Certificate of Location of Government Corner

ID#: 851309 **Description:** SEC CEN 13 85 **Date Set:** 11/4/77 **County:** Olmsted

Section: 13 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" rerod

Reference Ties:

The corner falls 2 1/2' west of centerline of N-S twp road and in line with fences east and west
County Survey Disk in S side square gate post NW 110.32'
County Survey Disk in PP #37493 NNW 109.35'
County Survey Disk in CP WSW 31.50'
This corner is located by GPS measurement

Corner History:

4-1903 Ch. Armstrong (P.49B) corner shown as stake now in road. 16 north stone 2x10x14 shown no meas. West line N 1/2 S 13 M&L 19.92-1/2. East line N 1/2 S 13 M&L 19.82 (not plain). 16 center NE 1/4 13 stake line to 1/16 east line N 1/2 13 a stone. 16 north west stake 9.94 west then 29.82 to 1/16 on west line N 1/2 13. RP: 1/16 east line N 1/2 13 Br. Oak N 30 W 1.32. 16 south (stake at 15.00) true 16 south stake M&L 19.90'. 16 center SE 1/4 13 stake shown.

11-4-1977 County Surveyor dug in center of road and in line with fence E&W with backhoe. Found old stake packed in stones 2-1/2' deep. Set a 1/2"x2' rod in the stake hole. Set a 1/2"x2' rod at the road surface. Corner 1.25 W and .7 S of t.n. Corner in centerline N-S road and 1' N of fences E and W. RP's: CSD in S side sq gate post in SE corner hog set up NW 110.32'. CSD in PP #37493 NNW 109.35'. CSD in CP WSW 31.50'. 1/16 N 11-3-77 dug with backhoe over M&L . Dug appx 3' W, 5'E, 4'N, and 4' S by 6' deep to clay. Found two boulders on clay but did not look like a set corner so did not tie in. Found nothing further.

10-19-1983 V. Fangman found and used 1/2" rerod.

8-6-1984 V. Fangman found and used 1/2" rerod.

2-22-2000 V. Fangman found and used 1/2" rerod.

5-30-2003 V. Fangman found and used 1/2" rerod.

8-27-2004 V. Fangman used computed center at intersecting quarter lines.

8-10-2005 County Surveyor found 1/2" rerod down 0.3' in good condition.

3-6-2006 V. Fangman used computed center of section 13, he also found 1/2" rerod 0.31' south and 0.06' east of computed location.

4-27-2007 V. Fangman used computed center at intersecting quarter lines.