Certificate of Location of Government Corner

ID#: 851405 **Description:** SEC COR 14 15 22 23 85 **Date Set:** 8/28/64 **County:** Olmsted

Section: 14 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls at fence corner to fences N-S-E-W
Center of lightning scarred 24" Burr Oak SW 5.5'
Center of 8" Walnut blazed SE 33.7'
This corner is located by GPS reference stations "Kundert A & B"

Corner History:

1854 Gov't Notes: John Cushing, Deputy Surveyor; 80.0 set corner. RPs- 15" black oak B S35W 48 links, 16" black oak B S82w 100 links. Dug trench.

1-1858 T. Hunter Pg.48 No.70; Used corner set 1/16 west for line north at 19.89. Also set property corner for line south at 19.78 then 20.0 west.

12-1894 W.Fraser Pg.556 No.513; Corner gone, no evidence, no bearing trees. Set stone in center of 2 other stones as corner.

9-19-39 J. Kerr used corner to set of find 1/4 14-15.

4-30-1948 J.Kerr Bk.37 Pg.23; Found corner. Set 1/4 15-22.

8-28-1964 J. Kerr set CIM over 1/2"x18" rod.

1-21-2003 County Surveyor found CIM down 0.3' in good condition.