Certificate of Location of Government Corner

ID#: 851509 **Description:** SEC CEN 15 85 **Date Set:** 6/21/1984 **County:** Olmsted

Section: 15 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1/2" pipe with cap RLS #14888

Reference Ties:

The corner falls in N-S fence
Rock pile S 11'
Center of large quadruple tree SSW 16'
This corner is located by GPS reference stations "D.O.T. A & B"

Corner History:

1-21-1858 T. Hunter, County Surveyor, (Book A, Page 48, Survey No. 70) shows center of section. 1/16th west 20.29 chains M&L to 1/4 post. BT's to 1/16th (N55°E 30 links (19.80')), (N84-1/2°W 32 links (21.12')). 1/16th east 20.05 chains M&L to 1/4 post. BT's to 1/16th (S54°E 56-1/2 links (37.29')), (S61-1/2°W 29 links (19.14')).

12-1-1894 W. Fraser, County Surveyor, (Book A, Page 556, Survey No. 513) set marked stake with boulder stone by its side at true intersecting lines. 16th west found stake 2 links too far east reset stake 19.40 chains (1280.40') M&L. 16th north drove stake 19.97 chains (1318.02') M&L. 16th east drove stake with boulder by side 19.86-1/2 chains (1311.09') M&L.

3-4-1966 Agneberg & Sankstone used computed center at intersecting quarter lines.

6-8-1979 T. Taylor found and used iron monument

9-14-1981 County Surveyor dug from a point 1/2' north and 1' east of the traverse nail set on the NW side of the corner post to fences north and west, north for 3' and east for 3'. Found old post hole 1.3' east and 1.3' north of the travers nail and when digging out the post we found what seemed to be the tip of the old stake (about 6") in the hole with the post. We found a 6"x8"x12" boulder about 1' NE'ly of the post hole. It appeared to have been disturbed. It was not standing up and we could not find a mark where it stood. It was just under the ground surface. Dug from a point 5' south of the traverse nail south for 7' to the corner post and west 3' +, found nothing further.

6-21-1984 V. Fangman set 1/2" pipe w/cap #14888 at intersecting quarter lines. He also found 3/4" rod 19.4' north and 5.61' east of center (probably Sankstone's center).

10-11-1991 V. Fangman found and used 1/2" pipe w/cap.

2-12-1993 V. Fangman found and used 1/2" pipe w/cap.

11-20-2002 V. Fangman used computed center at intersecting quarter lines.

9-9-2003 V. Fangman found and used 1/2" pipe w/cap.

9-15-2005 County Survey Crew found 1/2" pipe with plastic cap RLS 14888 up 0.1' in good condition and measured its position using GPS. Monument falls in N-S fence, corner post lying on ground, rock pile 11' south and center of large quadruple tree 16' SSW.

2-15-2006 V. Fangman used computed center at intersecting quarter lines.