Certificate of Location of Government Corner

ID#: 851604 **Description:** 1/4 SEC COR 16 21 85 **Date Set:** 10/14/1964 **County:** Olmsted

Section: 16 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of E-W fence
Steel fence post 1' E
Sign on railroad tie CP 1 1/2' NW
This corner is located by GPS reference stations "Koelsch A & B"

Corner History:

1854 Cushing, Deputy Surveyor; West on true line between 16 & 21. 39.99' set quarter section post. RP- burr oak 8" N3E 52 links. 79.98' to section corner.

12-1871 R. Perry by T. Hunter Pg.189 No.200; Corner gone, reset from witness trees. 16 south set stake, and 16 west set stake.

9-25-1964 J. Kerr ran section line. Due extensively along old fence. Balk in open pasture. Found nothing.

10-14-1964 J. Kerr set CIM over 1/2" x 3' steel M & L down 0.6'.

1-1974 Tom Ferguson found 3/4"x1" diameter iron rod in centerline CR. Also found pipe about 1.3' north of rod, pipe is on section line according to T. Ferguson's work and possibly set by T. Taylor's crew.

9-16-1981 1/16 west: County Surveyor started digging with backhoe over a point on line from SW 16 to SE 16 and at Hunter's measure from SW 16. Dug 7' deep to clay. There was no black dirt left. Had driven on clay, did not dig further.

2-23-2001 County Surveyor found CIM down 1' in good condition.

11-8-2006 County Surveyor found CIM down 1' in good condition.