Certificate of Location of Government Corner

ID#: 851609 **Description:** SEC CEN 16 85 **Date Set:** 5/31/99 **County:** Olmsted

Section: 16 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 6 1/2' south of E-W fence
Steel fence post 1/2' North
This corner is located by GPS reference stations "Hervey & Photo Pt #910"

Corner History:

8-1934 county highway department book #82 page 13 use something as center of sec it falls 603' east of centerline of co rd.

9-1964 J. Kerr (B.89 P.64 S.16) Jerry Westlund, very difficult line from S 1/4 north except last 80 rods. Staked out farm buildings from balance farm also staked out old creamery site in NE 1/4 21. Could have set 1/16 corner north of S 1/4 16, set 3/4" rod where N-S 1/4 line as run intersected angling road at 1768.45 in centerline road. Set redheads near center 16, found established fences, would be very difficult corner to set. No N 1/4 16 established in large open cultivated field. For this survey meas from center rock pile in line fence north at 1/16 east of NW corner 6 a recorded 1/16 corner east. 20.10 as recorded, did not correct line at center 16 corner at erect of heavly wooded area full of cyclone windfalls. Total mile 5272.87 ± last 80 rods stadia only.

5-31-1999 Vince Fangman set 1/2" pipe w/cap RLS #14888 at intersecting quarter lines.

8-14-2000 V. Fangman found and used 1/2" pipe.

1-9-2002 V. Fangman found and used 1/2" pipe.

11-20-2003 County Surveyor found 1/2" pipe w/cap RLS #14888 down 0.2' in good condition.

12-17-2004 V. Fangman found and used 1/2" pipe.

8-4-2005 V. Fangman found and used 1/2" pipe.

5-2-2006 V. Fangman used computed center at intersecting quarter lines.