Certificate of Location of Government Corner

ID#: 851804 **Description:** 1/4 SEC COR 18 19 85 **Date Set:** 6/3/80 **County:** Olmsted

Section: 18 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 9' south of centerline of E-W twp road and 1' west of fence north
County Survey Disk in E side CP NNE 42.49'
County Survey Disk in N side PP SE 61.00'
County Survey Disk in S side 24" Burr Oak up 5' NW 113.87'
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes: John M. Cushing, Deputy Surveyor. East on true course. 38.80 chs. Set 1/4 post from which a 5" jack oak B N45°E 30 links, 4" jack oak B. S15°E 58 links.

9-1856 Thomas Hunter, County Surveyor, (Bk.A Pg.16 No.26 abd Old Field Bk. 13 Pg.115) used this corner to set 1/16 east and probably to set the center 19.

8-1857 E.P. Bircher, Surveyor, per J.B. Fellows, Deputy, (Old Road Bk.--Rd No.66) surveyed the road on the west and north line of section 19.

2 & 3-1892 Thomas Fraser, County Surveyor,(Bk.A Pg.471 No.452 and Old Fieldbook 8, Pg.11) set a drag tooth at this corner on the line. Set a stake midway and on line at the 1/16 east and 1/16 west.

10-29-1971 County Surveyor dug and found nothing

6-2-1980 County Surveyor dug and found nothing.

6-3-1980 County Surveyor set CIM over a 1/2"x18" rod. This corner is 1 1/2' west of the fence line north and 7 1/2' south of the center of the E-W road. Set at prorated Gov't measure as per Thomas Fraser's survey No. 452.

3-23-1005 County Surveyor found CIM down 0.6' in good condition.