Certificate of Location of Government Corner

ID#: 851809 **Description:** SEC CEN 18 85 **Date Set:** 8/3/1989 **County:** Olmsted

Section: 18 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1/2" pipe w/cap RLS #14888

Reference Ties:

Iron post 0.5' north
This corner is located by GPS reference stations "Hoerle A & B"

Corner History:

3-1-1892 T. Fraser, County Surveyor, (Book A, Page 471, Survey No. 452) could not find N 1/4 18 so set center 18 on E-W 1/4 line at computed distances. Measured east 40.10-1/8 chains (2646.68') and west 39.10-1/8 chains (2580.68'). 16th south set stake M&L 29 links short gov't measure.

8-3-1989 V. Fangman set 1/2" pipe w/cap #14888 at intersecting quarter lines.

1-29-1997 V. Fangman found and used 1/2" pipe at intersecting quarter lines.

1-7-1998 V. Fangman found and used 1/2" pipe at intersecting quarter lines.

7-29-1999 W. Claassen used computed center.

4-10-2000 V. Fangman found and used 1/2" pipe at intersecting quarter lines.

10-30-2001 V. Fangman found and used 1/2" pipe at intersecting quarter lines.

1-20-2003 V. Fangman found and used 1/2" pipe at center of section.

9-13-2005 County Survey Crew found 1/2" pipe w/plastic cap RLS #14888 at surface in good condition and measured its position using GPS.

1-31-2006 County Survey Crew found 1/2" pipe at surface in good condition.

5-12-2011 Massey Land Surveying found and used 1/2" pipe at intersecting quarter lines.