Certificate of Location of Government Corner

ID#: 852005 **Description:** SEC COR 19 20 29 30 85 **Date Set:** 11/16/2012 **County:** Olmsted

Section: 20 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is down 0.4'
The corner falls 1.5' west of N-S fence and in line with fence east.
Sign nailed to RR tie corner post, East, 1.5'
This corner is located by GPS reference stations "Meyer C & D"

Corner History:

8-10-1854 Gov't Notes: John Cushing, Dept. Surveyor. 80.00 set corner to sections 19-20-29-30 from which. Aspen 12 in. B N33E 20 lks. J. Oak 6 in. B S32E 23 lks. Hichory 8 in. B S51W 28 lks. Aspen 7 in. B N43W 24 lks.

2-5-1877 T. Hunter (Book A, P.306 No.301) found stake standing with witness trees standing and marked stumps of rest of B trees. 16 east set stake M&L 20.12-1/2 1328.25' Wedge brook N 1/4°W meas north of above 1/16 to 1/16 between center and W 1/4 20 39.91. S 20'E meas south above 1/16 to 1/16 between center and W 29 39.96.

3-1-1892 Thos Fraser (Book A, P.472-473 No.452) run line from 1/4 17-18 to SE cor 19 39.88-5/9 each 1/2 mile 2632.4. 1/4 19-20 gone found stake at SE cor 19 had been very recently pulled up but had stood close to a post and avered by adjoining landowners, set new stake also tested by remains of NE BT N33°E 20 lks Aspen 12 took new witness tree SE 19 12" basswood N 5-1/2°E 22-1/2 L.

5-23-1910 Ch. Larson (Book B, P.124) survey as platted evidently platted with top of plat as east if so and top is east side sec 30 and not N-S 1/4 line of 30 then corner above NE cor 30 claimed as "post in ground". 16 south set iron rod M&L 19.89 1312.74' to 1/4 29-30 claimed as limestone found corner unrecored. No meas ever recorded, post in ground could be Thos Fraser stake by cor P P.473 or post.

6-4-2004 County Surveyor visited area of corner. Railroad tie CP to fences N-S-E.

10-5-2012 1/16th Corner South: County survey crew found 1 1/2" x 8" stone down 0.3' in good condition. The stone falls 30' west of N-S fence.

11-15-2012 County survey crew dug an area 5.5' West, 6' East, 3.5' North and 3.5' South around a RR Tie used as a corner fence post. The excavation was about 4' deep down to clay material. Found wood fragments and a circular shape of discolored soil on the southwest side of the corner post, down 3'. The dig area covered T. Fraser's line and distance from the north, double distance and line from the 1/4 corner Sections 29-30 over a stone found at 1/16th corner north and full T. Hunter measure from found iron at 1/4 corner Sections 20-29. County survey crew set a 6' telspar pipe with cast iron cap at the location of the wood fragments and discolored soil.