Certificate of Location of Government Corner

ID#: 852006 **Description:** 1/4 SEC COR 19 20 85 **Date Set:** 10/20/71 **County:** Olmsted

Section: 20 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

Row of 7 large pines running east S 50.8'
Row of large maples running east S 33.1'
Center of 18" Pine SE 56.8'
Bottle cap in NW side PP #23272 SW 37.66'
40D nail in SE side huge Elm NE 59.4'
Punched cross in W end 18" CMP SW 20.25'
Punched cross in E end 18" CMP SE 27.54'
Center of 4" Sugar Maple ENE 80.4'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor, North between sections 19 & 20. 40.0 set quarter section post. RPs- 6" aspen S28E 17 links, 4" burr oak N89W 9 links. 80.0 set section corner.

9-1856 Thomas Hunter pg.16 No.26; 1/16 east 20.07 1/2 chs. M & L,B.T.(N36°E 12 links)(N69°W 18 1/2 links) 1/16 west 19.93 chs. M & L B.T.s (East 1.76chs.)(S55 3/4°W 105 links), N-S 1/16 line in NW 1/4 20 measure 40chs. N-S 1/16 line in NE 1/4 19 measure 40 chs.

3-1892 Thomas Fraser Pg.473 No.452; Corner gone. Set drag tooth M & L. Set SE corner 18, RP-cross in large boulder N65°W 46 links.

6-1939 county highway department, Bk.100 Pg.2; Found stone monument and iron stake. RPs- disc in 12" elm NE 58.9, disc in 30" elm SE 41.6.

1951 county highway department Bk.191; Measured north to NE 19 and west to w 1/4 19. RPs-14" elmNE 41.9, disc pp SW 37.8(both gone in 1971)

10-18-1971 County Surveyor measured east from center county line blacktop. PI at 1735.0. Maple still in place, ash tree gone or boxelder south of tree row taken as witness. Measured east and found fence south at 2540.5, farm boundary fence at 2972.5, and centerline 1/16 road running south at 3858.0. Set 120d at 5186. county highway department assumed corner site. All reference points gone. Set small nail near 8' west as 00 for measure north. Used old well cave in topo +80'N L 32'. Measured north to 1/16 fence west (1309.5), should be 1317+. Set nail at NE 19.

10-20-1971 County Surveyor found limestones and iron drag tooth set by Thomas Fraser 3-1892 and county highway department 6-1939. Set CIM over 1"x24" axle shaft with L stone pieces by side of iron. Took measurements north and west.

7-21-2004 County Surveyor found CIM down 1.1' in good condition.