Certificate of Location of Government Corner

ID#: 852009 **Description:** SEC CEN 20 85 **Date Set:** 9/19/1856 **County:** Olmsted

Section: 20 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Limestone

Reference Ties:

The corner falls 1' S of CP to fences N-W-E
Sickle bar on south side
Sign on CP 1' north
This corner is located by GPS reference stations "Cow Chips A & B"

Corner History:

9-19-1856 T. Hunter (P.16 No.26) meas east 39.93 2635.38. Meas south 39.91 2634.06, meas west 40.15 2649.9 then 19.93 2630.76. show 3 BT's: N10°E 93 lks, S72-1/2°W 61 lks, S9-1/2°E 44 lks.

2-5-1877 T. Hunter (P.306 No.301) found stone set 1856 on subdivision of section. Tested B trees standing. 16 west found stake set survey no 26 set M&L. Meas south 39.82 2628.12'

8-1922 J. Kerr Book 1920 (22) P.18 found stone, drove sickle bar down beside stone. Run line from E 1/4 corner 20 2631.3 1856 R 39.93 2635.38.

12-1969 County Surveyor walked to corner from west with dep needle, got good iron indication just SE corner post 18" ±.

9-1973 County Surveyor, found 2"x8" top limestone with Kerr's sickle bar on S side of stone (top of stone down about 2") corner lies ± 1.5' ESE of cor of fences E-W-N-S. Used center of stone as corner and projected line from W 1/4 cor 20 over center 20 (this stone) to set 1/4 cor 20-21 line was projected by elec traverse.

6-10-1985 V. Fangman found and used 2"x8" limestone.

5-19-2003 V. Fangman found and used 2"x8" limestone.

2-27-2004 V. Fangman found and used 2"x8" limestone.

7-21-2004 County Surveyor found 2"x8" topped limestone at surface in good condition. Set sign in cp 1' north.

5-10-2006 V. Fangman found and used 2"x8" limestone.