Certificate of Location of Government Corner

ID#: 852104 **Description:** 1/4 SEC COR 21 28 85 **Date Set:** 7/7/72 **County:** Olmsted

Section: 21 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of centerline of CR 105 and 4' east of centerline of field drive north
Concrete nail in E side 10" Oak post S 28.11'
Bottle cap in N side PP #23033 WSW 137.35'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Cushing; 40.0 set temporary 1/4 section post west on true line between sections 21 & 28 V9° 15'E. 39.99 set 1/4 section post. RPs- 6" aspen 13N 36W 20 links, 18" burr oak 13S E 79 links.

5-1863 Compton Pg.70 No.99; Stone with cinders on plat, used to set center 28.

10-1969 Perk Higham, Dodge County Surveyor set iron rod flush road surface for SE corner.

12-4-1969 J. Kerr found SE 21.

10-15-1971 County Surveyor found pipe and set 5/8"x30" rod. Rps- 28.11' south to head of concrete nail east side 10" oak corner post, 137.35' WSW to pepsi cap north side pp #23033, corner east of fence couth near center of road. Corner lies 1.6' south of a direct line between the section corner stones.

Pipe was 1.47' east and .25' south of a rod used in a survey as assumed corner

7-7-1972 County Surveyor set CIM over pipe.

5-15-1979 County Surveyor shot CIM for county highway department

2-16-2001 County Surveyor found CIM down 0.7' in good condition.

8-10-2006 County Surveyor found CIM down 0.6' in good condition.