Certificate of Location of Government Corner

ID#: 852105 **Description:** SEC COR 20 21 28 29 85 **Date Set:** 12/1/69 **County:** Olmsted

Section: 21 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence and 1/2' SE of CP
Scar on 26" Hard Maple SW 16.0'
This corner is located by GPS reference stations "Newell A & B"

Corner History:

1854 Gov't Notes: John Cushing, Deputy Surveyor: 80.0 set corner post. RPs- 10" burr oak N71W 18 links, 12" aspen S31E 43 links, 6" burr oak N85E 17 links.

6-1910 Charles Larson Pg.126 B; Found stake, drilled hole 2 1/2' deep and filled with limestone. Set stone on top. South set stake at 9.97 chs. Then 9.97 to 1/16 corner and set up same as above section corner. Found 1/16 stake. West set oak stake at 9.95 set M & L

7-1910 Charles Larson Pg.130 B; Found stake and lime filled hole. Set stone on top 16x20x20

8-1922 J.Kerr Bk.19,20,& 22 Pg.18; Run line between sections 20-21, corrected line. Ran west to center south 20 and found stone and sickle bar beside stone.

12-1-1969 J. Kerr set CIM over iron in lime hole with original stone on south side.

3-28-2001 County Surveyor found CIM at surface in good condition.

6-7-2004 County Surveyor found CIM at surface in good condition.