Certificate of Location of Government Corner

ID#: 852106 **Description:** 1/4 SEC COR 20 21 85 **Date Set:** 10/23/81 **County:** Olmsted

Section: 21 **Township:** 108N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #8952

Reference Ties:

The corner falls 1' south of fence west and 2 1/2' west of N-S fence
Spike in CP ENE 3.3'
Spike in SW side brace post SE 6.4'
This corner is located by GPS reference stations "Fuchs A & B"

Corner History:

1854 Gov't Notes: John Cushing, Deputy Surveyor, North between sections 20 & 21. 40.0 chs. Set 1/4 sec. post from which 5" burr oak S46 °E161 links. Made trench. 80.0 chs. Section corner.

9-1856 Thomas Hunter, (Bk.A Pg.16 No.26 and Old Fieldbook 13 Pg.115) used 1/4 post to set center of 20 and 1/16 west of the center of 20.

12-1871 Robert Perry, Thomas Hunter, Deputy, (Bk.A Pg.189 No.200) found 1/4 post standing and tested it by witness tree and found correct. Set 1/16 north.

2-1877 Thomas Hunter, (Bk.A Pg.306-307 No.301 and Old Fieldbook 4 Pg.28-30 and 168-171) found stone at center 20 and 1/16 north stake.

6-1883 Thomas Hunter, (Old Fieldbook 14 Pg.8) may have used this corner to run the E-W 1/4 line section 21.

8-1922 John Kerr, (Kerr Bk.9 Pg.17-18) set point midway and on line between section corners. Drove sickle bar in ground beside stone.

9-1973 County Surveyor set 1/2"x30" pipe. RPs-nail in top of corner fence post S 12.1', 30p spike in 12" elm tree NNW 36.0'.

10-23-1981 County Surveyor found 10"x12"x22" boulder over a stake. Drove 1" square pipe with cap in the stake mark and set stone on south side and accepted as 1/4 corner. Pipe is 3.5' east and 13.3' north of the corner found.

2-28-2001 County Surveyor found 1" square pipe w/cap at surface in good condition.