Certificate of Location of Government Corner

ID#: 852204 **Description:** 1/4 SEC COR 22 27 85 **Date Set:** 8/21/86 **County:** Olmsted

Section: 22 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in N side 16" Hard Maple ENE 29.68'
County Survey Disk in E side 9" White Oak N 48.52'
Post w/sign 1' north
This corner is located by GPS reference stations "Hodge C & D"

Corner History:

Gov't Notes: 40.00 - 40.00 Aspen 12" S20W 22 lks (14.52), W Oak 12" N7°E 30 lks (19.80).

1-17-1985 Vince Fangman found old post stub at fence corner. Drove steel fence post. Also found K. Ewers spike, will send cert for more information (location of Ewers spike).

8-15-1986 County Surveyor most westerly fence coming in from the north is 13' west of Vince Fangmans post. Dug and found post stub in fence line west 7.4' W of Vinces post. Dug from 2' E to 15' W of Vinces post 1' S and 3' N of line running west, clay and bedrock were down about 1/2 ft, found nothing. Also dug at M&L which is 9' W of the most westerly fence, found nothing. No trees in the area could be the witness trees.

8-21-1986 County Surveyor dug under westerly fence (now midway) N&S of line, conditions terrible, rocks close to surface, found nothing. Accepted location of Vince Fangmans post stub. Line from NE 22 over center 22 indicates this is the post used by Kerr. Set telpar pipe with CIC at this location and survey marker sign and post 1.0 north. RP's: Spike and CSD in N side 16" hard maple ENE 29.68'. Spike and CSD in E side 9" white oak N'ly 48.52' in line with fence west.

8-16-2005 County Surveyor found cast iron cap on telspar pipe in good condition.