Certificate of Location of Government Corner

ID#: 852206 **Description:** 1/4 SEC COR 21 22 85 **Date Set:** 8/27/64 **County:** Olmsted

Section: 22 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of E-W fence
Nail in hub in 12" Elm N 35° W 20.5'
20d spike in root 18" Elm blazed N 40° E 32.6'
Post w/sign 2' South
This corner is located by GPS reference stations "CC Ski A & B"

Corner History:

1854 Gov't Notes: Cushing, 40.0 set 1/4 section post. RPs' 12" lima 13S 67W 24 links, 8" black oak 13N 45E 11 links.

1-1858 T. Hunter Pg. 48 No. 70 shows 1/4 post.

12-1871 T. Hunter by R. Perry Pg.189 No.200; Found stake standing, tested by witness trees used only for E-W 1/4 line in NW 1/4 section 21.

8-1928 J. Kerr set stone.

8-1964 J. Kerr set CIM over 3/4"x12" rod over old stake found from remains of bearing tree and stone, stone is .2'x.15'x1.3'. RP's-Hub nailed to 12" elm with wires on east side tree crotches 14' up N35°W 20.5', fence line running E & W N 2.0, 20d in 5'x2' elm root pointing to corner, natural blaze toward corner tree 18" in diameter N40°E 32.6'.

12-23-2003 County Surveyor found CIM at surface in good condition. Set post w/sign 2' South.