Certificate of Location of Government Corner

ID#: 852304 **Description:** 1/4 SEC COR 23 26 85 **Date Set:** 12/3/73 **County:** Olmsted

Section: 23 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 6 1/2' north of E-W fence
Pk nail & disc in W side 18" Basswood NE 27.62'
Pk nail & disc in top fence post S 6.70'
Pk nail & disc in W side 20" Basswood SE 21.60'
This corner is located by GPS reference stations "Deer A & B"

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor; West between sections 23 & 26. 40.0 set quarter section post. RPs- 12" black oak S48°W 46 links, 12" black oak N48°E 54 links.

11-1887 Thomas Hunter (Pg.424 No.413) County Surveyor found stake from SW bearing tree and stump of NE bearing tree. Drove new stake in its place.

5-1895 William Fraser (Pg.570 No.413), County Surveyor found stake remains east of corner post and tested with stumps of witness tress.

12-13-1973 County Surveyor found wood stake. Drove an iron stake in place of wood stake and set a CIM over all.

1-22-2003 County Surveyor found CIM down 0.4' in good condition.

3-25-2005 Yaggy Colby Survey Crew found monument in good condition.