Certificate of Location of Government Corner

ID#: 852305 **Description:** SEC COR 22 23 26 27 85 **Date Set:** 9/1/1986 **County:** Olmsted

Section: 23 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 34' east of centerline of Douglas Trail
This corner is located by GPS reference stations "Feil A & Photo Pt. #901"

Corner History:

1854 Gov't Notes: John M. Cushing, Deputy Surveyor, at 80 chs set corner of section 22-23-26-27 raised mound with trench as per instructions and drove charred stake.

5-1857 T. Hunter, town of New Haven survey shows stone at SW cor sec 23.

1972 Tom Ferguson set 1/2" iron as corner by doubling his corners at 1/4 cor 23-26 over iron at fence corner at 1/16th west of 1/4 cor being 1328 - 1328.

12-1973 County Surveyor found stake and set CIM at 1/4 cor 23-26 .44' S and 1.95' west of T. Ferguson cor.

6-1978 County Surveyor traversed the north lineof the NW 1/4 of sec. 26 and adjusted the sec. cor.

8-1986 County Surveyor dug and found stone 3"x15" top, 6"x6" bottom, 15" long, down 4'. Put steel fence post stub and flat iron by stone. Set cast iron cap on telspar pipe over and survey marker sign and post 1' north.

1-22-2003 County Surveyor found cast iron cap on telspar pipe at surface in good condition.

2-15-2008 County Surveyor found cast iron cap on telspar pipe down 0.1' in good condition.