Certificate of Location of Government Corner

ID#: 852404 **Description:** 1/4 SEC COR 24 25 85 **Date Set:** 6/17/67 **County:** Olmsted

Section: 24 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2 1/2' south of E-W fence
Nail and disc in CP NW 4.7'
Bed rail is .45' east of CIM
Post w/sign 2' north
This corner is located by GPS reference stations "Guyer's A & B"

Corner History:

1854 Gov't Notes: 40.0 set temporary 1/4 section post west on true line between sections 24 & 25. 40.0 set 1/4 section post, V9° 11' E. RP- 4" oak N50 W 25 links

4-1871 Found stake averred by Mr.Murphy as original corner. Set stone in place of stake. Corner lies 55 links north of direct line.

2-1882 T. Hunter Pg.374 No.365; Found stone Pg.181 used to set center S25

10-1890 T.Fraser Pg.446 No.431; Didn't look for corner. Used fences etc and Hunter's notes at near center 25. Set boulder 10x13x16 on E-W 1/16 line at 90 rods west of 1/16 corner on twp line.

5-1895 W. Fraser Pg.571 No.523; Found stone set Pg.181. West drove stake M & L 19.82, then 9.91 then 9.91 to section corner. Set wood stakes at plat corners in NW 1/4 25.

1-1933 J.Kerr Bk.8 Pg.35; Found boulder stone. Set stones about it.

6-16-1967 J.Kerr; Found stone 5x6x16 limestone with boulder. Set CIM above 1 1/4x24" pipe with bed rail up 3' on north side. Limeston on north side , boulder on east side, and trash.

10-1985 County Surveyor set up point at T.H. measure from the S 1/4 cor and on line to M&L at the N 1/4 cor 24. Pt came in N-S fence line. Dug 5' E, 2'W, 1'N and 1-1/2' S but did not find anything. Used to be N-S road here, where did fence come from?

8-22-2005 County Surveyor found CIM in good condition down 0.6'. Set sign and post 2' north in fence line.