Certificate of Location of Government Corner

ID#: 852406 **Description:** 1/4 SEC COR 23 24 85 **Date Set:** 7/3/2003 **County:** Olmsted

Section: 24 **Township:** 108N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 3 1/2' north of centerline of CSAH 12 and 3' west of fences north and south
This corner is located by GPS reference stations "Klopp A & B"

Corner History:

1854 Gov't Notes: Cushing, 40.00 set 1/4 section post from which a White Oak B S 72 W 55 links. White Oak 18 in. N 72 E 45 links.

4-1871 R. Perry by T. Hunter (P.181 No.192) found stake in center road claimed where original stake stood. 16 south 20.00.

6-1892 Thos. Fraser (P.468 No.450) corner gone, set stake M&L 39.78-1/3 2625.7'. 16 north set stake 19.89-1/6 1312.9' comes 5' into river 12" Bl Oak S45°E 15 links.

1935 county highway department (B.86 P.78) found pointed boulder with iron pin on west side. RP: 12" Br Oak S 32.5 R Oak SW 46.5, Sp Oak SE 42.05, Sp in 8" Oak 40.7 took in hub SW 71.65, 24" drill steel with hub above as corner. Stone and rod in place.

1940 J. Kerr (B.17 P.1) used corner post as NW 24. SW 24 stake at F corner. Set 5/8" rod in road after digging 1/2 day for county tied corner on M&L 2624.81. Sp White Oak N 40.16, Sp Br Oak NW'ly 107.65 on 6-1947 B.34 P.40 S.14 set NW cor 24 well point.

1956 county highway department (B.219) indicates ties to cor stone indefinate.

6-1-1977 County Surveyor dug on S side of rod in blacktop, road cut, found nothing. Ready for CIM

1-28-2003 County Surveyor found 3/4" rerod down 0.3' in good condition.

7-3-2003 County Surveyor set 1" square pipe w/cap at surface over 3/4" rerod.

6-25-2008 County Surveyor found 1" square pipe w/cap at surface in good condition.