Certificate of Location of Government Corner

ID#: 852409 **Description:** SEC CEN 24 85 **Date Set:** 12/3/2008 **County:** Olmsted

Section: 24 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Mag nail

Reference Ties:

The monument is at the surface
Nail falls 3' north of centerline CSAH 12 and 4' east of centerline driveway south.
This corner is located by GPS measurement.

Corner History:

4-5-1871 R. Perry by T. Hunter (P.181 No.192) set stake inters line from all 1/4 corners. Meas east 39.52 2608.32, south 19.62 (1294.92) M&L then 9.81 M&L to S 1/4 corner.

1-21-1892 T. Fraser (P.468 No.450) did not set true corner as transit broken by accident after completing E-W 1/4 line. Set stake on said line 39.52 chs 2608.32 west of E 1/4 24. North set stake midway, no meas, no line.

6-7-1977 K. Ewers found and used RR spike.

10-1985 County Surveyor found Keith Ewers RR spike under BT overlay on CR 12 2.03 N and 10.36 W of t.n. (in centerline and in line fence N and 2-1/2' E of CP in S side of road).

10-29-1985 County Surveyor dug from t.n. (set in centerline E-W road and in line fe N) for 1' + N, 1' S, 1' E and 2' west to check this location for Hunter's stake and check conditions for larger tractor dig. There was a road down 1-1/2' then 1-1/2 ' to clay but very mixed to clay. Found nothing and conditions poor for larger dig.

11-22-1985 McGhie & Betts set p.k. nail at center of section.

2-13-1989 T. Ferguson found and used pk nail.

1-28-2003 County Surveyor visited area of corner. Found nothing.

12-3-2008 V. Fangman set mag nail at intersecting quarter lines as center of section 24.

3-15-2012 County survey crew found mag nail in good condition.