Certificate of Location of Government Corner

ID#: 852504 **Description:** 1/4 SEC COR 25 36 85 **Date Set:** 9/30/1966 **County:** Olmsted

Section: 25 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 26' NW of centerline of twp road on curve, in line of centerline of twp road east and 5' east of fence north
Bottle cap in PP NW 45.0'
Nail & hub 22" Elm blazed NE 45.4'
Center of very large Elm N 68.5'
Post w/sign 2' NW
This corner is located by GPS measurement

Corner History:

1854 Cushing; 40.0 set temprory 1/4 \section post west on true line between section 25 & 36 V9° 15'E. 40.0 set 1/4 section post. RPs': 12" aspen W27 E48 links, 8" oak S27 W26 links.

5-1867 H.E. Horton Pg. 83 No. 127 shows 1/4 cor.

2-1882 T. Hunter Pg.374 No.365; Found remains of old stake in line fence north averred by A.Clason as site of true corner. North set stake.

6-1899 Robert Fraser Pg.643 No.579; Found boulder with stake below, placed by Mr. Holmes on old stake to preserve corner, testimony by Mr. Clason. 16 east drove stake M & L.

9-1966 J.Kerr; Set CIM over original boulder, rods on E-W sides. Also, original stake, small stones, and glass.

8-10-2005 County Surveyor found CIM down 0.8' in good condition. Set post w/sign.

2-15-2008 County Surveyor found CIM down 1.1' in good condition.