Certificate of Location of Government Corner

ID#: 852506 **Description:** 1/4 SEC COR 25 26 85 **Date Set:** 12/4/73 **County:** Olmsted

Section: 25 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 105 1/2' north of centerline CSAH 3 on curve
16d spike in S side 12" Spruce NE 56.85'
Pk nail & disc in W side PP SW 10.43'
16d spike in W side 12" Basswood SW 39.24'
Post w/sign 2' south
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor; North between sections 25 & 26. 40.0 chs set quarter section post. RPs- 18" black oak S50°W 12 links, 8: ash N37°E 37 links. 80.0 chs. To section corner.

2-1882 Thomas Hunter (Pg.374 No.365), County Surveyor states corner gone. Set a stake from witness tree stumps. Took two bearing trees.

11-1887 T. Hunter (Pg.424 No.413) reset stake from 2 bearing trees taken Pg.374.

5-1895 William Fraser (Pg.571 No.523), County Surveyor found old stake and stumps of witness trees given Pg.374. Drove new stake with stones on 2 sides.

6-1899 Robert Fraser (Pg.643 No.579), County Surveyor found stake.

1950's McGhie found stone.

1967 McGhie found stone. Set 1 1/2" iron pipe

12-4-1973 County Surveyor found pipe. Dug and found stake and several stones near pipe. Removed stones and drove pipe down 30" and set CIM over pipe.

3-25-2005 Yaggy Colby Survey Crew found monument in good condition.

8-10-2005 County Surveyor found CIM down 1' in good condition. Set post w/sign.