Certificate of Location of Government Corner

ID#: 852509 **Description:** SEC CEN 25 85 **Date Set:** **County:** Olmsted

Section: 25 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

2-13-1882 T. Hunter (P.374 No.365) set stake inters lines White Oak 8" S45°W 4 lks 2.64'. South set stakes at 4.94 (326.04) then 24.70-3/4 (1630.7) then 9.88-1/4 (652.2) to stake. E-W 1/4 line N87°42' W = N-S 1/4 line N2-1/4°E total meas south 39.53 2609.0 ±

10-1-1890 Thos Fraser (P.446 No.431) found marked stake set by Hunter. Tested by B tree in place. East set stake on line and 90 rods west of E 1/4 25.

5-10-1895 W. Fraser (P.571 No.523) found stake and BT P.365. 16 west drove stake M&L 20.01-1/2 1321.0. BT: 10" Br Oak N84-1/2°E 8 links. Drove stakes west of above 1/16 cor M&L 10.00-3/4 and stakes 15.99 1055.34 and then 11.99-1/4 791.5 then 11.99-1/4 791.5 (2638.34). North of above 1/16 corner also stakes 15.96 then 11.97 then 11.97. North of 1/64 corner west of above 1/16 corner all in NW 1/4 25.

6-2-1899 Robert Fraser (P.643 No.579) found stake and BT White Oak S45°W 4 lks. 16 east drove stake M&L 19.92-1/2 1315.05' to CIM.

9-27-1977 K. Ewers found and used 8" drag tooth.

5-27-1983 V. Fangman used computed position.

7-22-1997 Vince Fangman set 1/2" pipe w/cap RLS #14888 at intersecting quarter lines.

11-25-1998 V. Fangman used computed center at intersecting quarter lines.

1-4-1999 V. Fangman found and used 1/2" pipe.

12-6-2000 V. Fangman found and used 1/2" pipe.

8-22-2005 County Surveyor found pipe lying flat on the ground near corner post.