Certificate of Location of Government Corner

ID#: 852606 **Description:** 1/4 SEC COR 26 27 85 **Date Set:** 10/13/71 **County:** Olmsted

Section: 26 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 11' north of centerline of E-W twp road and in line with fence south
Bottle cap in S side PP #23611 ENE 76.98'
Concrete nail in W side CP ESE 88.25'
5/8" rod under fence in ring of stones S 75.0'
Pk nail with disc in W side old fence post SSW 45.22'
Pk nail with disc in E side PP SSE 41.32'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: 40.0 set 1/4 section post in mound with trench,pits,and drove charred stake.

11-1887 T. Hunter Pg.424 No.413; Found stones in center road. Took quarry stone as true corner. Which Charles Osborn avers he set by old stake.

5-1895 W. Fraser Pg.570 No.522; Found stone set Pg.424. 1/16 east set stone.

8-2-1971 County Surveyor found 3/8" rod set by Mcghie.

10-13-1971 County Surveyor found 3/8" rod in center of road set by McGhie and boulder. Found L stone 4x6x19 with boulder 10x11x14 on south side. Set 5/8"x18" iron below CIM with L stones on N & S sides.

8-24-1993 County Surveyor found CIM in good condition in line of fence south and 11' north of centerline E-W twp road.

4-24-2000 County Surveyor found CIM down 1.3' in good condition.

3-25-2005 Yaggy Colby Survey Crew found monument in good condition.