Certificate of Location of Government Corner

ID#: 852609 **Description:** SEC CEN 26 85 **Date Set:** 2/9/2009 **County:** Olmsted

Section: 26 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the monumented center of section.

1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CSAH 3 and in line with fence south
The monument is at the surface
County Survey Disc in SW side PP #23587 NW 54.89'
This corner is located by GPS measurement

Corner History:

11-21-1887 Thomas Hunter, County Surveyor, (Book A, Page 424, Survey No. 413) set 4"x6"x18" quarry stone at intersecting quarter lines. RPs - 8" Cherry N32-1/2°W 26 links (17.16'), 6" Jack Oak N52°E 38 links (25.08'). 1/16th South set stake midway and on line at 19.96-1/2 chains (1317.69') to South 1/4. 1/16th East set stake midway and on line at 20.10 chains (1326.60') to East 1/4.

5-9-1895 William Fraser, County Surveyor, (Book A, Page 570, Survey No. 522) found stone and witness trees. 1/16th West set 2"x6"x18" stone midway and on line at 20.06-1/2 chains (1324.29') to West 1/4.

10-13-1971 Roger Brand, County Surveyor, (New Haven Field Book A, Pages 215-218) 1/16th West found 2"x6" topped stone down 1.8' in good condition. Measured east-west quarter line and found stone to be 0.32+/- south of quarter line. RP - Spike in PP WNW 136.16'.

12-12-1973 Roger Brand, County Surveyor, (New Haven Field Book A, Pages 219-224) set RR spike on east-west quarter line and by doubling the distance from the West 1/4 to the 1/16th corner which nearly matches north-south quarter after finding North 1/4.

5-29-1981 Zenk Engineering found and used RR spike.

9-27-1983 Zenk Engineering found and used RR spike.

9-12-1984 Vince Fangman found and used RR spike.

11-4-1988 Vince Fangman found and used RR spike.

2-2-1990 McGhie & Betts, Inc. found and used RR spike.

3-8-1990 Vince Fangman found and used RR spike.

11-18-1992 Vince Fangman found and used RR spike.

1-23-1995 Vince Fangman found and used RR spike.

4-4-1996 Vince Fangman found and used RR spike.

10-22-1996 Yaggy Colby Associates found and used RR spike.

9-17-1998 Yaggy Colby Associates found and used RR spike.

6-16-1999 Vince Fangman found and used RR spike.

7-22-2002 Vince Fangman found and used RR spike.

12-17-2003 Vince Fangman found and used RR spike.

9-24-2004 Vince Fangman found and used RR spike.

4-19-2005 Yaggy Colby Associates used computed center at intersecting quarter lines for Minnesota Department of Transportation Right of Way Plat No. 55-90.

8-10-2005 County Survey Crew found RR spike down 0.3' in good condition and measured its position using GPS.

5-21-2008 County Survey Crew found RR spike down 0.3' in good condition referenced its position for bituminous overlay road project.

7-7-2008 County Survey Crew found and removed RR spike.

2-9-2009 County Survey Crew set 1" square pipe w/cap at surface from bituminous overlay road project tie out.

3-14-2012 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.

3-15-2012 County Survey Crew found 1" square pipe w/cap at surface in good condition.

10-18-2012 WSN found and used monument.