Certificate of Location of Government Corner

ID#: 852704 **Description:** 1/4 SEC COR 27 34 85 **Date Set:** 8/24/93 **County:** Olmsted

Section: 27 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 14' west of N-S pasture fence
20d spike in 24" Ash NNW 37.28'
Stone by J. Kerr W 26.69'
Pole barn spike in 6" Elm SW 4.85'
Post w/sign 1' N
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Cushing, 40.00 set temp 1/4 section post. West on true line between section 27 and 34, variance 9°34'E. 40.00 set 1/4 section post. Aspen 12 in. 5'S W 40 links. Black Ash 8 in. N 15 E 14 links.

6-1946 J. Kerr (B.30 P.57) set stone 2x7x16 with old stake by side packed with stones. South found stone 2"x5"x?" in place at 327.63'. 16 south 1" pipe 3.5' long at 1306.65 set M&L 22" hackberry SW 16.6. 22" hard maple N 64.7 with fence wires wrapped around. Center 34 south accepted corner post at 2633.1. 1/16 north of center 34 Sta. 3940.65, Sta. N 1/4 34 5246.63. Meas N 1/4 34 east to NE 34 2660.0 ± on line 327.63 south. 1/4 corner stone set by projecting line from 1/64 stone found. 327.63' (identical meas as on east line of NE 1/4 34) north on N-S 1/4 line started at S 1/4 34 over stones and irons of village of Genoa over center 34 (could have been stone) setting 1/16 corner north of center 34 computing meas from 1/64 stone found. Points in Genoa used 1 stone found 551.1 north of S 1/4 34. SW corner block 4 from no 1 381.0 R 383.4 1931 survey 384.6. S 1/4 34 to center 2633.3, center to 1/16 1306.65, center to 1/4 stone 2285.7, stone N to 1/4 cor set 327.63'.

8-17-1993 County Surveyor visited corner found John Kerr 2x7x16 stone packed in stone 41' west of N-S fence found Vince Fangman (1988) tree ties and retied RP's: Ash NE 42.34 VF 42.44. Oak NE 25.41 VF 25.55. Elm SW 9.33 VF 9.23.

8-24-1993 County Surveyor dug at midway and line pt. 27' east of stone by J. Kerr. Found 2" diameter stake hole with wood pieces 16" deep into clay. We dug from 6' north of stake to 5' south and 2-1/2' east and west of stake. Average depth of 3' to clay the top of stake hole was 2.6' deep. Set cast iron cap on telspar pipe at stake hole location. RP's: V. Fangman 20d spike in 9" elm WSW 34.30'. V. Fangman 20d spike in 24" Ash NNW 37.28'. Stone by J.Kerr W 26.69'. Pole barn spike in 6" elm SW 4.85'. The corner falls 14' west of N-S pasture fence. Set sign and post 1' north

8-24-2005 County Surveyor found cast iron cap on telspar pipe in good condition down 0.3'. Located all ties but did not check distances.