Certificate of Location of Government Corner

ID#: 852806 **Description:** 1/4 SEC COR 28 29 85 **Date Set:** 3/24/2004 **County:** Olmsted

Section: 28 **Township:** 108N **Range:** 15W **Monument Description:** 1 1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 6' east of centerline of CR 105 and 1' south of fence east
This corner is located by GPS reference stations "McGee I & II"

Corner History:

1854 Gov't Notes: Cushing, 40.00 set 1/4 section post in which White Oak 8 in. S35 E39 links. Burr Oak 8 in. S38 10W links.

1863 P.C. Compton (P.70 No.99) shows 1/4 corner used to set center section 28 at intersecting lines.

1-1895 W. Fraser (P.590 No.536) found stake set earlier survey in place of stake set by Hunter from original stake. 16 south set stake M&L 19.95 1316.7'. 16 west set stake M&L 20.07 1324.6' with stake west as 1/64 at 10.03-1/2 662.3' M&L.

6-1910 Ch. Larson (P.126B) set oak stake, no details or measurements. 16 north set oak stake which is 19.86 1310.76 S of NE 29 CIM now. 16 center NE 1/4 29 found stake, drove hole 2-1/2' deep filled with lime, set limestone on top with meas of east 1984 and north 1988 poorly explained survey as usual.

7-1910 Ch. Larson (P.130B) reset corner from meas P.590, evidently N-S-W on running N-S line between 28-29 found this to be 25 lks 16.5' east of direct line accepted W. Frasers meas. W.F. meas 39.90 south 2633.4, east not W.F. 39.82 2628.12. Note indicates meas north 40.22 2654.52 when he set large limestone and lime hole below where CIM lies 1970. This corner not one believe can be found, not easily. Indicates corner lies east of direct line 25 lks 16.5'.

4-24-2000 County Surveyor visited corner location. Found nothing.

3-24-2004 Vince Fangman set 1 1/2" pipe w/cap down 0.4' as per County Surveyor's instruction.

6-1-2004 County Surveyor found 1 1/2" pipe w/cap down 0.4' in good condition.