Certificate of Location of Government Corner

ID#: 853009 **Description:** SEC CEN 30 85 **Date Set:** 11/22/88 **County:** Olmsted

Section: 30 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe with cap RLS #14888

Reference Ties:

20d spike in 3" Elm NNW 11.99'
20d spike in triple Boxelder ESE 8.36'
Post with sign 2' north
This corner is located by GPS reference stations "Venhuizen B & C"

Corner History:

11-6-1874 T. Hunter Pg.264 N0.262; Set stone 3x5x24 M & L 19.92 with property corner stake at 6.30 chs. Measured south and north.

10-20-1971 County Surveyor found stone. Set stone on east side of limestone. Dug small trench to head off erosion. Found 1/16 east 10"± above ground.

11-22-1988 Vince Fangman set 1/2" pipe over limestone.

1-8-1993 V. Fangman found and used 1/2" pipe.

12-6-1996 V. Fangman used computed position. Notes that limestone falls 0.20' S of computed position.

10-29-1999 David G. Rapp found and used monument at center of section 30.

6-29-2004 County Surveyor found 1/2" pipe w/cap up 0.4' in good condition. Set post with sign 2' north.