Certificate of Location of Government Corner

ID#: 853204 **Description:** S 1/4 SEC COR 32 85 **Date Set:** 7/20/2004 **County:** Olmsted

Section: 32 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3 1/2' north of E-W fence and in line with N-S fence
30d spike in 12" Oak ESE 43.87'
30d spike in 15" Elm NE 34.47'
Post with sign 2' south
This corner is located by GPS reference stations "Kunkel C & D"

Corner History:

1854 Gov't Notes; 40.0 set quarter section corner. RPs- 12" black oak N36° E54, 14" burr oak 14 S78° E 17.

4-1875 T. Hunter Pg.269 No.267; Found original stake. Tested stumps of bearing trees. 16 east set stake and 16 north drove short stake M & L.

6-1910 Charles Larson Pg.128 B; Found stone .

1935 county highway department Bk.78 Pg.75 Found square limestone at fence corner.

4-9-1971 County Surveyor ran & measured line from S32-33 CIM west. Found stone.

4-14-1971 County Surveyor measured from west stone at S1/4 31, 5313.2 so reset S31-32 midway at 2656.6.

3-28-1990 Vince Fangman found limestone 4' north of corner post under N-S fence. Drove a 3" wood post ± 1' north. RPs- 43.87' to 30d spike in 12 " oak ESE, 34.47' 30d spike in 15" elm NE.

7-20-2004 County Surveyor found 4x6x27 stone down 0.2' in good condition. Removed stone and set 5' telspar pipe w/cast iron cap up 0.2'. Set post with sign 2' south.