Certificate of Location of Government Corner

ID#: 853209 **Description:** SEC CEN 32 85 **Date Set:** 5/6/04 **County:** Olmsted

Section: 32 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 2' NW of large steel angle iron CP
This corner is located by GPS reference stations "Venhuizen D & E"

Corner History:

4-15-1875 T. Hunter (P.269 No.267) set stake at true inters right lines. 6" aspen S74°W 16 links (10.56), 12" aspen S33-1/2°E) 47 links (31.02). 16 east set stake M&L 19.96 1317.32', 8" J. Oak N22°W 15 lks, 10" J. Oak S74-1/2E 51-1/2 lks. 16 north set marked stake M&L 19.96 1317.32' 8" aspen N22°E 29 lks, 8" aspen S57°E 20 links. 16 center NE 1/4 32 set marked stake M&L 19.99 on N-S 1/16 8" Jack Oak S50°E 11-1/2 lks.

5-6-2004 V. Fangman set 1/2" pipe w/cap RLS #14888 at intersecting quarter lines.

2-13-2006 County Surveyor found 1/2" pipe w/cap RLS #14888 down 0.1'.