# Certificate of Location of Government Corner

**ID#:** 853404 **Description:** S 1/4 SEC COR 34 85 **Date Set:** 4/27/89 **County:** Olmsted

**Section:** 34 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 8 1/2' north of fence east and in line with fences south and west
30d spike in 6" Elm S 28.53'
30d spike in 8" Elm SE 48.87'
30d spike in 10" Elm SE 32.97'
Sign on CP 1/2' east
This corner is located by GPS reference stations "Schaefer A & B"

**Corner History:**

8-1853 Gov't Notes, John Ball, Deputy Surveyor West between sections 3 and 34 40.00 chs. Set quarter section post 14" hickory N30°E 50 lks. 8" hickory S25°W 10 lks.

5-1866 Edward Doud, Measured 131.38' north to SE corner of lot 7, Blk. 7 in platting of Genoa.

12-1897 William Fraser, County Surveyor (Pg. 614, No. 558) Found stumps of both bearing trees, and remains of old stake which agreed with stumps. Set new stake with stone by its side in place of old stake. Chained west 39.72 to section corner.

12-1916 John Kerr, Deputy County Surveyor (Bk. B, Pg. 264) found stone and stake, measured west 2616.5' to section Corner which he set midway and online between quarter corners.

1931 John Kerr, County Surveyor (bk. 6, pg. 3) used corner in survey of lots in Genoa. Measured west 5224.68' set south 33, 34 midway and online, did not use corner set in 1916.

9-1935 County Highway Department (bk. 78, pgs. 10,74) Found 2"x6" limestone above ground about 3" and 8' north of fence east, and inline with fence west. Found stone and stake 552.3' north.

6-1946 John Kerr, County Surveyor (bk. 30 pgs. 57-59) used corner measured north 551.1' found stone monument at main st. Measured north to center of section 34 2633.3'.

6-1951 John Kerr, County Surveyor (bk. 52, pg. 7) used corner measured north 419.1' to the SE corner of lot 7, blk 7 plat of Genoa. Measured from south quarter corner to NE corner of blk 7, set a 1¼" pipe at said corner.

9-1966 John Kerr, County Surveyor (bk 94, pg 61) used corner stone measured west 2334.7' to river bank. Measured south 2624.0' to corner post used as center of section.

12-1970 County Surveyor (New Haven bk A, pg 245) Found corner stone measured west 2620.3' to William Fraser stone and stake set in 1897.

6-12-84 Vince Fangman Found 4"x10" limestone, also found stone with angle iron over stone set by Merit Patterson in 1981 8' south, used 4"x10" stone measured east 2625.76' to CIM at section corner.

4-27-89 Vince Fangman set 24"x2" telspar pipe with cast iron cap in place of 4"x10" limestone found in 1984. Measured east 2624.70' to CIM at section corner.

8-26-93 County Surveyor found telspar pipe with cap in good condition.

4-12-2004 County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition. Set sign in CP 1/2' east.