Certificate of Location of Government Corner

ID#: 853505 **Description:** S SEC COR 34 35 85 **Date Set:** 7/7/72 **County:** Olmsted

Section: 35 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of N-S fence and 11' north of fence east
15" Burr Oak N4°W 25.8' (now about 32" tree)
40d in W side 18" Oak near root up 10" ± E 4.5'
Post w/sign 2' east
This corner is located by GPS reference stations "Tarara A & B"

Corner History:

1853 Gov't Notes: Ball, Deputy Surveyor, West between sections 2 & 35. 80.0 chs. Set section corner post. RPs- 15" burr oak N4°W 39 links, 25" burr oad S46° W 100 links, 8" aspen N68 1/2°E 30 links, 20" black oak S44°E 47 links.

county highway department (Book 78) searched for corner but found nothing. Used corner post of fences.

10-1969 McGhie & Betts found original NW bearing tree still standing. Dug carefully and found stake hole at near record measure from bearing tree. Drove 1/2" rod in stake hole as corner.

7-7-1972 County Surveyor found McGhie's iron. Accepted it as corner. Set CIM over railroad spike with limestones on north, south, and west . CIM down 2".

4-12-2004 County Surveyor found CIM down 0.3' in good condition. Set post w/sign 2' east.