Certificate of Location of Government Corner

ID#: 853506 **Description:** 1/4 SEC COR 34 35 85 **Date Set:** 9/8/76 **County:** Olmsted

Section: 35 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' NE of CP to fences N-S-E-W
County Survey Disk in twin Box Elder NW 37.02'
County Survey Disk in E side 15" Cherry N 5.07'
County Survey Disk in SW side 8" Burr Oak NW 97.97'
Post w/sign 2' north
This corner is located by GPS reference stations "Befort A & B"

Corner History:

6-1854 Gov't Notes: John M Cushing, Deputy Surveyor, North between sections 34 & 35. 40.0 chs. Set 1/4 section post, raised mound, dug trench, and drove charred stake.

1-1862 S. McDowell Pg. 67 No. 94 used corner to breakdown west 1/2 section 35.

2-1882 Thomas Hunter (Pg. 373 No.364), County Surveyor found the original stake in mound at the corner of the fence.

9-3-1976 County Surveyor dug around the corner post and found an old stake on the NE side. Set a 1/2" pipe in place of the stake.

9-8-1976 County Surveyor set CIM over the 1/2" pipe set 9-3-1976.

8-29-2005 County Surveyor found CIM in good condition at surface. Monument falls 1.0'± NE of corner post that is leaning SW for fence N-S-E-W. All old ties gone except spike and CSDin 8" Burr Oak but almost grown over, did not recheck. CSD with concrete nail in east side of 15" Cherry north 5.07' and CSD with concrete nail in Twin Box Elder NW 37.02'. Set sign and post 2.0' north.