Certificate of Location of Government Corner

ID#: 853509 **Description:** SEC CEN 35 85 **Date Set:** **County:** Olmsted

Section: 35 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe

Reference Ties:

The corner falls 12' E of centerline of N-S twp road

Corner History:

1-5-1862 Samuel McDowell (P.67 No.94) shows center sec. BT's to center N27°E 51 lks, S57°E 59 lks. See survey for breakdown of sec 35.

2-3-1882 T. Hunter (P.373 No.364) set stake inters lines. 10" J. Oak N83°W 73 lks, 6" J. Oak N32°W 51 lks. 16 north small J. Oak tree M&L 19.96 (1317.36) N1° 55' E. 16 west set stake M&L 20.25 1336.5'. 10" J. Oak N5°W 29 lks, 15" J. Oak N74-1/2W 40 lks. 16 center NW 1/4 35 set stake M&L 20.15 1329.9 on E-W 1/16 line 6" J. Oak S35°W 44 lks 6" J. Oak N40°W 14 lks.

1-1902 W. Fraser (P.28B) found stake on west side of road.

9-7-1976 County Surveyor dug from 2' S of traverse nail north and from 7' E of t.n. east. Dug 3-1/2' + into clay, evidence of road approx 2' deep. Much sediment beneath, found nothing. Digging on line from N 1/4 35 to nail at S 1/4 35.

11-17-1999 V. Fangman used computed center.

12-23-2002 Land Consultants found 1/2" pipe at center of section. Used pipe for breakdown of SW 1/4.

1-27-2005 County Surveyor found 1/2" pipe leaning west. Monument falls on east shoulder of road.