Certificate of Location of Government Corner

ID#: 933205 **Description:** S SEC COR 31 32 93 **Date Set:** 5/28/1986 **County:** Wabasha

Section: 32 **Township:** 109N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 9' north of E-W fence and 13' east of fence north
This corner is located by GPS reference stations "Wesson A & B"

Corner History:

9-27-1853 Gov't Notes: Elisha Norris, Deputy Surveyor; west corrected on south side of section 32. 80.0 chs set post for corner to section 31 & 32. Burr Oak 10" N57°W 117 lks, Burr Oak 10" N20°E 52 lks.

5-5-1986 Vince Fangman searched area and found a 2" pipe 33.26 west of set C.I.M. This pipe was assumed to have been set by Agneberg-Sankstone in January of 1970. It appears that this pipe was set midway between the S 1/4 of sec 31 and 32. This position does not fit the occupation lines to the north.

5-28-1986 Vince Fangman, C.I.M. was placed bringing the occupation lines down from the NE corner of the SE1/4 NE 1/4 sec 31. Mr. Marlin Graves told us that the new fence on the east line of his property was placed in the same place the old fence and willow tree line. Mr. Graves owns the E 10.0 acres of the S 1/2 SE 1/4 sec 31. We dug a 4'x16'2' hole by hand along the old fence line but found nothing but old wire. This hole extended from the set C.I.M. to the west beyond new fence. No original bearing trees were found.

8-9-2007 Olmsted County survey crew found 2" O.D. pipe up 0.3' in good condition.

10-30-2007 Olmsted County survey crew found CIM down 0.1' in good condition.