Certificate of Location of Government Corner

ID#: 933405 **Description:** S SEC COR 33 34 93 **Date Set:** 7/19/2012 **County:** Wabasha

Section: 34 **Township:** 109N **Range:** 13W **Monument Description:** Telspar Pipe with Cast Iron Cap

Reference Ties:

The corner falls in centerline of E-W twp road and in line with fence north
This corner is located by GPS

Corner History:

9-26-1853 Gov't Notes: Elisha Norris, Deputy Surveyor; west corrected on south side section 34. 80.0 chs set post in mound with charred stake, trench, pits, and cherry stones planted at each angle for corner to sections 33 & 34.

7-5-2007 Olmsted County Surveyor found nothing.

8-8-2007 Olmsted County Surveyor visited area, did not find anything. Set concrete nail down 0.2' from computed coordinates.

7-19-2012 Olmsted County Surveyor dug with a backhoe and found a wedge shaped stone down 3.3' with the point facing up. The base of the stone measured 10"x6" with a height of 10". Directly below was another, larger stone which was also in an upright position. The second stone measured 12"x6" with a height of 24". The stones were located at the centerline of an E-W township road and in line with fence north. Removed the stones and replaced with a 6' telspar pipe with cast iron cap, down 1.3'.