Certificate of Location of Government Corner

ID#: 933604 **Description:** S 1/4 SEC COR 36 93 **Date Set:** 8/6/2012 **County:** Wabasha

Section: 36 **Township:** 109N **Range:** 13W **Monument Description:** 1" Square Pipe with Cap 42638

Reference Ties:

The monement is at the surface.
The corner falls 1' north of centerline of CSAH 11
This corner is located by GPS reference stations "Wet Sock & 820607"

Corner History:

1853 Gov't Notes: Elisha Norris, Deputy Surveyor; West corrected on south side of section 36. 40.0 chs. Set quarter section post in mound with charred stake, trench, pits, and cherry stones planted north and south.

5-11-1976 Olmsted County Surveyor dug and found the remains of a stone 8"x5"x3" with the top worn smooth. No other stones in the area. Set a 3/4" bolt under stone and a small bolt at the road surface.

3-12-2007 Olmsted County Surveyor visited area of corner, found nothing.

8-9-2007 Olmsted County Surveyor computed a position of the 3/4" bolt from 5-11-1976 by using the 1976 traverse data. Olmsted County survey crew set pk nail at surface at the computed position.

8-6-2012 Olmsted County survey crew found PK nail and checked coordinates. Replaced it with a 1" square pipe x 2' long with cap no. 42638.