Certificate of Location of Government Corner

ID#: 943204 **Description:** S 1/4 SEC COR 32 94 **Date Set:** **County:** Wabasha

Section: 32 **Township:** 109N **Range:** 14W **Monument Description:** 1" iron

Reference Ties:

The corner falls 2' north of E-W fence and 1' west of fence north
Pop cap in W side fence post S 3.89'
This corner is located by GPS reference stations "Prokasky A & B"

Corner History:

1853 Gov't Notes: Elisha S. Norris, Deputy Surveyor; West corrected on south side of section 32 40.0 set quarter section post in mound with rock (14x6x4) trench, pits, and cherry stones planted N & S.

1854 Gov't Notes: Michael Karrick, Deputy Surveyor; North on true line between sections 4 & 5; 80.82 chs. intesected Standard Parallel No. 2 970 links east of quarter section post on south boundary of section 32 in Twp 109 North of Range 14 west 5th Principle Meridian and set post for corner tosections 4 & 5. Erected mound with trench, pits, and osage orange seeds at each angle.

4-1910 John Rafter, Surveyor, (letter to Thomas Fraser) measured 9.70 chs from the N-S fence at north section corner 4-5 to a fence marked for standard 1/4 corner section 32.

4-1983 Olmsted County Surveyor found 1" iron 4' north of E-W fence and 640.22 west of north section corner 4-5.

6-1983 Olmsted County Surveyor dug at location of iron and found nothing.

10-22-2002 County Surveyor found 1" iron rod w/cap up 0.2' in good condition. Corner falls 2.0' North of E-W fence and 1.0' West of fence running North.