Certificate of Location of Government Corner

ID#: 943505 **Description:** S SEC COR 34 35 94 **Date Set:** **County:** Wabasha

Section: 35 **Township:** 109N **Range:** 14W **Monument Description:** RR spike above cast iron monument

Reference Ties:

The corner falls 6' south of centerline of twp road on curve and 9' west of centerline culvert
This corner is located by GPS reference stations "Ryan's Bay and 840208"

Corner History:

12-9-1895 W.Fraser Pg.586 No.534; Needed to set the N 1/4 2 and N 2-3, but couldn't find any evidence so measured and ran line from N 1-2 (stone set by Hunter) in place of stake to N 3-4(stake by T.Fraser in place of Gov't stake) and set N 2-3 on line and prorated Gov't measure and then N 1/4 corner 2 midway and on line.

1910 Letter from Rafter to T.Fraser states corner in field and found nothing, but finds stones at N 1/4 and N 2-3.

1916 Power Dam Survey; shows no stone at S 34-35, but measure of 657' west from N 1/4 corner 2 to S 34-35 and straight line from N 1/4 corner 2 to N 2-3.

5-26-1925 J. Kerr Bk.25 (-6) Pg.9; Kerr finds NE 2, N 1/4 2, 1/16 W of N 1/4 2 and measured this 3/4 mile, but doesn't mention section corner 34-35.

6-6-1964 John Kerr found stone at N 1/4 2-108-14.

7-1964 John Kerr found stone at N 1-2.

8-10-1964 J. Kerr, Wabasha Book Pg.32; From N 1/4 corner section 2 AZ 270°13' 657' for section corner 34 & 35. Surveying pg.61 used corner to survey road into Dream Acres plat.

4-6-1967 J. Kerr, Book 93 Page 40, shows CIM inplace at the SW corner of Section 35-109-14. (Additional details regarding the origin of this monument are unknown. The Olmsted County Survey Department staff believe it was most likely set by John Kerr, in or near 1964)

Date unknown: N 1/4 card; measure 657.0 west to CIM set as south section corner 34-35, T109 R14. N 2-3; after 1972 survey CIM at S 34-35- may now be a little north of line.

12-17-2001 During their Mazeppa Township Remonumentation Project, Johnson & Scofield, Inc. recovered a 4 inch cast iron monument 0.8 feet below the surface of the road with a railroad spike sitting on top of it. After analyzing field and record data, the found monument was accepted as the best perpetuation of the Original Public Land Survey corner. Wabasha County HARN 96 coordinate from Wabasha County Certificate of Location: North=132006.743 and East=446409.485

9-27-2005 County Surveyor found RR spike down 0.4' in good condition.