Certificate of Location of Government Corner

ID#: 943605 **Description:** S SEC COR 35 36 94 **Date Set:** **County:** Wabasha

Section: 36 **Township:** 109N **Range:** 14W **Monument Description:**

Reference Ties:

The corner falls 8' north of centerline of E-W twp road 13 1/2' east of centerline of residential driveway north and 3 1/2' west of fence north
This corner is located by GPS reference stations "Nietz A & B"

Corner History:

9-27-1853 Gov't Notes: Elisha Norris, Deputy Surveyor; west corrected on south side of section 36. 80.0 chs set post for corner to sections 35 & 36. Burr Oak 8" N32°W 75 lks, Burr Oak 10" N11°W 77 lks.

5-13-1879 Thomas Hunter (Page 359, No. 350) found stone

1909 John Rafter, County Surveyor, states that he set a gas pipe deep in the ground at 80.34 chains south of an iron stake at the Northeast corner of Section 35 T.109 R.14 and 80.12 chains west of an iron rod at the Southeast corner of Section 36 T.109 R.14.

10-8-2001 Johnson & Scofield, Inc. excavated a 10'x10'x4' deep area with a county backhoe at the intersection of the centerline of a township road and north fence line. Dug through an old road bed approximately 3 feet down and found nothing. After analyzing field and record data, the temporary corner position at the intersection of the north fence line and centerline of the town road was accepted as the best perpetuation of the Original Public Land Survey corner. Two 1"x18" iron pipes were set, one on top of the other, with a 2 inch diameter Wabasha County cast iron cap affixed to the top of the top pipe. Wabasha County HARN 96 coordinates from Wabasha County Certificate of Location: North=131962.755 and East=451654.949

9-27-2005 Olmsted County Surveyor visited area of corner, found no monument in place.

8-1-2012 Olmsted County survey crew visited the area of the corner and found nothing