Certificate of Location of Government Corner

ID#: 953504 **Description:** S 1/4 SEC COR 35 95 **Date Set:** 11/5/1996 **County:** Goodhue

Section: 35 **Township:** 109N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of centerline of E-W twp road and 19' west of centerline of field drive north
County highway disk in SW side U.G. pedestal SE 80.92'
This corner is located by GPS measurement

Corner History:

9-1853 E.S. Norris, U.S. Deputy Surveyor, set a charred stake in mound of earth with trench and pits.

1854 John Cushing, U.S. Deputy Surveyor, ran north between Sections 1 and 2, T108N, R15W, and intersected the 2nd Standard Parallel 11 chains 15 links east of the quarter section post of Section 35, T109N, R15W, 5th P.M.

5-1868 H. Clark, Pine Island Township Clerk, recorded a Plat and description for a road to run on the County line between Goodhue County and Olmsted County beginning at the South Quarter post of Section 35 and running east to the St. Paul and Elliota road.

10-1996 Dennis L. Robinson, Goodhue County Deputy Surveyor, supervised the excavation for the corner at the intersection of east-west road and 2634 feet east of the Southeast Corner of Section 34. An area 8.5-feet by 18.5-feet by 3-feet deep was searched no evidence was recovered. An analysis of the record and field evidence indicates the corner can be re-established by the 1868 road survey and the boulder at the closing corner of Sections 1 and 2.

11-5-1996 Goodhue County monument was set on line between the Southeast and Southwest Corner of Section 35, which agrees with 1868 road survey and 11.15 chains west of the said closing corner.

7-7-2001 Olmsted County Surveyor found CIM in good condition down 0.3'.