Certificate of Location of Government Corner

ID#: 953604 **Description:** S 1/4 SEC COR 36 95 **Date Set:** 11/5/1996 **County:** Goodhue

Section: 36 **Township:** 109N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' north of centerline of E-W twp road and 2' west of fence north
County highway disk in E side CP N 49.09'
This corner is located by GPS measurement

Corner History:

9-1853 E.S. Norris, U.S. Deputy Surveyor, set a charred stake in mound of earth with trench and pits.

10-1853 John Ball, U.S. Deputy Surveyor, intersected the 2nd standard parallel 11 chains 19 links east of the South Quarter Corner Section 36. He set a charred stake in mound of earth to mark the Northeast Corner Section 1, T108N, R15W.

5-1868 H.G. Clark, Pine Island Town Clerk, filed a Plat of Survey for a road to run east on the County line from the South Quarter post of Section 35 and intersect with the St. Paul and Elliota road.

9-1996 Dennis L. Robinson, Goodhue County Deputy Surveyor supervised the excavation for the corner at the intersection of the east-west road and fence line north. An area 10.5-feet by 14-feet by 4-feet deep was searched. A few fieldstones were found but none were considered to have been set. The search area appeared to have been previously disturbed. An analysis of the record and field evidence indicates the corner can be re-established by using the found Northeast Corner of Section 1, T108N, R15W, and measuring 11.19 chains west along the 2nd Standard Parallel. This location is confirmed by a property division fence line along the west line of the Southeast Quarter of Section 36 and the 1868 road order for a road to run on the County line.

11-5-1996 Goodhue County monument was set to help mark and perpetuate the Public Land Survey corner.

7-7-2001 Olmsted County Surveyor found CIM down 0.5' in good condition.

2-15-2006 Olmsted County Surveyor found CIM down 0.3' in good condition.