11-12-1971 set 3/8 x 4' rod as corner post. line and measure west. (1)

#430606

1/4 corner east 1/4 / Hi Forest 104-14

5-1902 2# Fraser P16B S1 104-14, south lines of Secs. 34-35-36 John Beach, Robt Sutton, John McBride.

found old stake in center of mound
drove iron stake in place of stake.

-16 west set stone 3 x 5 x 15" N&L no meas.

-16 north set stone on line and gave corp. north 20.08 3/4 (1325.77 then 71.92 1/2 (1183.05'

-16 center NE 1/4 / set corner at inters of 1/16 lines

(over)

the N-S of this line came very close or maybe a little south of record from north and 5.75 west of fence wire N 20 1/16 corner north would come up to 9' east of corner post of fence running west which should be exact - dug nearly 5 or 6 feet east into clay but not 9'
S side of NE 1/4 E 1/2 1339.55 - N side E 1/2 1363.65
Mean measured be 1356.6
KP E'41 4.47 SW to conc. rail on SE side large power Pole
12.78 NNW to conc rail on NE side oak brace Pole pf fe. N
1.0' S to main line of new fence running east
5.75 W to " " old " " north

Gov't Notes Ball 1853
40.00 set quarter section post and built mound and drove stake and planted osage orange seed in S.E.

Card # 2 East 1/4 1 High Forest 10 4-14 (2)
#-506006
9-27 found stone at center 1 and 1/16 stone N of center 1 at 1313.75 (record) could not find anything at 1/16 east of center -
10-27 ran aerial ℄ N-S 1/16 line of NE 1/4 1 from 2 stones found set straddle points at E-W 1/4 line
11-12 found 1/16 stone west of center 1346.9 near comp record
ran and meas projected line east very carfully set 1¼" x 3½' iron pipe at inters of line at 1339.55 with long steel fence post beside pipe.
- cont line ℄ meas east to double meas 1339.55 2679.1
- set 3/8" x 4' rump rod with one block over rod as witness iron stamp stone below when rod still up 10"+ left was many rocks of all sizes in this area as found before (over

9-14-1971 Co surv.. drove to corner. had electronic detector. much erosion fill from fields north 2' or more stones of every size & shape next to corner post and huge transmission power pole with large ground cable and stake. ground all mixed with wire pieces so working wouldn't work in detector line. dug large area 3' deep.
- Meas west to find 1/16 stone and center sec l. 1/16 area in bogs and deep hummocks, fences all over may be 10 or 15' off.
- tied up meas on nail meas in 9-13 from north at 1300.
Meas 2686.7 which came about midway betw fences N & S
- Corner lost unless can be reproduced between Twp corner and 1/16 stone north.
9-16 Meas & run line from NE1 (Twp cor) south found 1/16 fence running west at exact record 1183.05 and Sedge large corner post of fence north (not south) at record of 1325.77 - Line run from center corner post to NE1 mon. fell 6' or more into field east.

Lee card 2

Card #3 East ¼ | High Forest 107-14 #430033 (3)

5-15-95 Found 3/8" Iron up ± 10" set in 1971 by Co Surveyor in line of fence west, 1½ No of fence East & ±5' East of fence So

6-12-95 Set CIC/P² @ 3/8" rod location by Roger Brandl Co Surveyor in 1971 at which time he ran the E-W ¼ line of sec 1 and divided his 1/16th pipe to set the 3/8" rod. The corner falls in line of fence west and 5' East of line of existing fence south & 1½' North of fence East.

CSO in fence post west 6.60

CSO in witness post So 7.82'

Set sign and post to North