1 9-1-71 set C.I.M. over 5/8" rod. #440107 (1)

section corner. north 1-2 Hi Forest 104-14. 5-1902 Fr Frazer P16B & 1104-14. south lines of & 34-35-36 105-14. John Beach, Robt Sutan John McBride set temp stake at this corner. on line betw & W 35 and & E 35 and on a line projected from & W 1 over W 1/4 1 intersecting the E-W line.

- 16 south set temp stake on sec line at post pop south 18.87 & 1245.42' then 19.87 1318.42 to W 1/4 1.
- meas east to & 1/4 35 (set M & L stake) 4.87 (321.42.
- meas west to N 1/4 2. (stone & road) 40.37. (2664.42'
- 16 east. set stone 4x5x18. M & L 20.78. (1371.48) over)

-16 center NW 1/4 1. set stone at true witness lines.

8-24-71 Co surv. meas east from iron rod at S 34-35 105-14
set nail at 978.69 record 1/2 2664.42 (1332.21 - 353.52) which
came just east side of fence on east side of road south.
set nail at 2300 should be 2310.9 from west. 1371.48 from 1/16 E.
9-1-71 after finding N 1/4 1 and 1/16 west 104-14 and drag tooth
at S 1/4 35 and setting S 35-36 then reset N 1 = 2.10 H
set C/M over 12" deg over 5/8" rod and metal pieces.
RPs. 160.4 E on slope meas to pepsi cap on S side power pole.
140.0 W on slope meas to orange cap on S side
3.9 N to eyeball line of south edge power poles east.
5.0 ± N to E-W fence.
the power pole east 160.4 is the pole that comes about 8'
west of eyeball line of east line of power poles running north.

HI FOREST SECTION CORNER 1-2 #440107 #2

Gov't Notes Ball 1853

78.98 Intersected 1st. Standard Parallel 250 lks. west of ¼ section post to south section 35. set post
Black Oak 8in. S-80 W-52lks.
Bur Oak 7in. S-50 E-14 lks.