X 8-8-1974 Set CIM over ½"x12" rod in place of ½" rod fd. #440406 (1)

1/4 corner 4-5 Hi Forest 104-14

5-1878 Hunter P343 no 337 S4 H D Morse & others.
found large boulder shown & anerd by 21 m Carlson as
having been set in exact place of orig stake.
-16 North set stake N&L 19.87½ as instructed 1311.95' N1¾°W
-16 east set stake N&L 20.12½ (1326.6 N87°W 1328.25'
-16 Center NW 1/4 4 set stake miters lines
- bearing south to corner established N10W

4-1906. Ch Armstrong P104B NW 1/4 S4. AL Brush.
found recorded corner. [1328.58' 1287.0 2615.6 ft.
-1/16 north set boulder stone at 20.13 chen 19.50 to N W 4.
-16 east set boulder stone N&L 20.10 to corner fence past at Center 4.

1940 Co Hwy Dept. B 112 P1 B 109 - P9. 11L4-5 104-14

½" rod other stone and stake found. Meas west 5302.4

Dixie fence post E 33.45'.

" tele pole SW 50.95'

corner is PI for road north - Meas north 2614.3 R. 2615.6R.

5-1950 J Kerr field book 46 P72. local survey 45' used corner for line west for local acreage layout. likely untied county corner.

1931 Co HD B6 P25. Subcorner stone.

FP each 331 — FP SW 49.1

Meas N- 2614.9. To N Cor 4-5' R. 2615.6

6-22-71 found rod used as corner. dug with tractor found numerous subs & nails & 4 or 5 small boulders (Most length 8") down over 4' near red clay subsoil.

Card #2. 1/4 4-5 High Forest 104-14. #440406 (2)

6-22-71 Meas east. found 1/16 fence north at 1326.0 and 1/4 fence N & S at 2655.8 R. Hunter 1328.25 M & L
Charmichael 1326.6 M & L

Could not find position boulder at 1/16 corner, many boulders at center & some 18" deep, no wash or fill ever. found very old corner post some 2' south of fence west in line fence N & S and nearer line of willows east than fence west.

- 6-25-71 dug north of rod up to 6' as line east might indicate found nothing at all. replaced rod as found. Large boulder gone

- Meas north to projected line from 1/16 stone found on N-S 1/4 line north of center & to hub, 1334.8 R 1328.58

- Meas north to Quad hub at N-4-5. 2614.2 R to 2623.5 Corn. 2615.6 county 2614.3. (over

1/4 4-5 104-14

6-28-71 found N 4-5 stone set 1878.
Meas now from iron at 1/4 4-5 north to stone. at N 4-5.
.2616.5. with nail set in black top on projected line from
1/16 stone N 4 center 4 over N edge corner post at center NW 1/4
S.H. at 1334.8 south R. 1328.58 North. 1281.7 R. 1287.0.
total of 2616.5 against R 2615.58 compares favorably.
- must consider iron in place at. 1/4 4-5 correct as placed.
MHD disc in power pole.

N.W ~~S.W~~ ~~4315~~ 4567
E 33.09.
NE ~~40.56~~ 40.56

(N.W.cor. fence post
6" sq. Tel-Box - S.W. - 48.2)
MHD disc in power pole

Corner center reads S, W, N and line fence east.
It is very evident that 1/16 corner east would come as much as 5' or more south.

#440406 (3)

1/4 corner 4-5 High Forest 104-14

R.P.'s to C.E.M.

M.H.D. disc in pp	N.W. 45.67
Fence Post	E. 33.09
M.H.d disc R.P.	N.E. 40.56
NW cor 6" Sq. tele box	S.W. 48.2'

Corner falls in the center of the N-S - & W. roads - in line with the fence running East.

C.H.D. - 1925 Book # 38 Page 89 Shows Stone

Gov't Notes Ball 1853
North between section 4 & 5.
40.00 set ¼ section post and deposited charcoal and raise mound of earth and sod. Cut trench from wich a stone 4 x 6 feet S-23 E-37 lks.