X - 10-19-72 set CIM over orig stone and 12" gals to it. ①
#440505
section corner south 5-6 Th Forest 104-14
6-1878 Hunter P348 no 341 S 6 C L Goodrich + others
did not use corner or go to it.
Caption (armstrong) a S. Cavil avers in 1866 that he set a
red cedar post 6x6x40" in old stake hole in the bog and
on digging 2' deep found a foot of old post well preserved.
set new post and stone. July 1 1900 E H Armstrong.

1940 Co Hwy Dept. stake in road.
Sp - tile hole NE 44.2 - (No county record 1-1969)
" cor fence post SE 48.2.


1960 De Val. Minn Hwy Dept No Good
found stone down 6" 3½" x 7" x 7" on ℄ N-S-E roads

over)

State
RPS

fence post NW 75.7.
tree No Good SW 67.0

1-1969 at County MHD Dace · boulder in place · 6" willow fence post · SW No Good. NW 7ft.b.

6-28-71 Co surv. found 6" farm tile 12" long filled with concrete with 5/8" iron rod, in center, in center Road intersection N-S-E. - dug with tractor found many stones from 3" up to 18" dia. In fill - found stake by one (not vertical). - dug 7' deep to peat bog bottom 8'x6'x5'  for the cedar stake recorded in bog. found nothing. filled hole and replaced tile & rod. Corner center T inters nothing of any description To tie to. Consider Case closed and to line Lists & Cards 1/16 W 26546

11-29-71 Meas N to Le W 982.5', to Cente B bp 26522,

Card # 2. South 5-6 High Forest 104-14 (2)
#440505
Meas north of 982.5 to 40D Rail 1312 east of 1/16 stone 995.8
Meas North rail in center blacktop 18.8 W of iron rod 2652.20
Record chas Armstrong 40.31 or 2660.46
Meas north to inters of line from west + 2.42 or 2654.60
11-29-71 Meas east from iron at S 1/4 6 2660.7 R 2665.1
12-8-71 dug with Keller back-hoe at S 5-6 and found large recorded boulder. 24x18x16 with cross cut on top. and part of 5x5x36 cedar stake near top of stone
- found stone 6.3 south and 4.9 west of iron in tile
Meas N now 995.8., 2658.5 and 2660.92.
- ran & meas line north from rod in tile random line
- set 5/8" x 30" rod over stone found - left iron in tile in place
frozen over

line of course 4.9 E at S.5.6
8.72 E at 1312.0 E of 1/16 slope.
18.8 E at rod accepted as 1/4 S-6
Computed on actual line would come 15.1 W of 18.8 or
33.9 west of road for likely corner used by Armstrong
who says in unrecorded book that 1/4 S-6 is boulder
16"x12"x12" which served as corner for 20 years in
southeast corner of intersection. Apparent location 33.9±
west of center road intersection.

40.~~63~~ SE to punch mark in S end 24" galv culvert } Westerly of 2 N-S culverts
43.4 NE to top center of N end 24" galv culvert }
84.88 ESE to punched cross in S end 30" galv culvert } easterly of 2 N-S culverts
88.23 ENE to punched cross in N end 30" galv culvert }

10-19-72. Set C/N over 12" galv bolt. Removed. Over tube & rod. no further R.P.s.