6-12-79 CIM Is this final? Cut held in Blue Book (1)

#450207

section corner. North 2-3 Hi Forest 10 4-15
6-1877 Hunter P 319 no 313 S 3 J. Brewer J. Saulsberry
J. Rickett.
all corners on range line between SE cor 34
and SW cor 33 gone. (all but stone at NW cor 3
SW cor 33 stake. SE 34 orig stake in mound.
- Meas line 160.53 chs. set marked stake at section corner
south 33-34. Midway 80.26 but 40.25 from 1/4 33-34
not on a direct line SE 34 & SW 33.
set stake at S 1/4 34 M & L 40.13. 5.00 E of N.2-3
thence as NE 3 set stone 5X10X15 exactly 5 chains
west of S 1/4 34 as set on range line SW 34 to SE 34.
- length of line from stone NE 3 to stone NW 3 80.04
- also set marked stake at N 1/4 3 M & L 40.02 bearings over.

Bearings of lines on range line as set.

S W cor 34 to S E cor 34 as set N 89°10' W.

S W cor 34 to S W cor 33 " " N 88°45' W.

→ this could be to NW 3; beware!

Gov't Notes Ball 1853

78.64 Intersected 1st. Standard Parallel 500 lks. west of ¼ section corner on south boundary of section 34 township 105 North range 15 West 5th. Principle Meridian. Made mound with trench and drove charred stake in center and planted apple tree seed in N.W. corner.

1979 Ranon BK, Pages 63, 87, 90

Page 63: 5-22-79 Went to N.2-3. The fence posts had been removed and there is a power line running south and East. We measured 500 lks West from the fence Note at the S¼ Cor 34, Rock Dell and set a nail to shoot in line into the power pole running East Could not find the spot where old corner post stood.

(cont.)

#450207 (2)

Section Corner North 2-3 High Forest 104-15
(1979 Remon Cont.)

Page 87 6-11-79 Dug at Will Fraser's measure from the E-W ¼ line Sec 2 (West ½) and also from the N ¼ Cor 2. Found recorded 5x10x15" boulder 1' deep with a stake a post hole beneath. Set a ½" rod where the stone stood and set the stone on the North side of the rod. Left the hole open for CIM. Corner 1.6 W and 4.9 South of the t.n.

Page 90 6-12-79 Returned here and set a CIM over the iron set June 11. There is a large boulder on the South side of the C.I.M. and a Survey Marker Sign .85 ENE the corner is 4½' South of the power pole line East. RP: CSD S. side pp# 24845 NE 14.05

Held Cnt in Blue Book until the S. 1/4 Cor 34 or S. 33-34 is found or set so corner can be put on proper line if that's what we want.

8-10-95 Fd CIM in good shape. Post & sign had been destroyed by cutting equipment. We set new post & sign 1' North of CIM. Tie to PP #24845 is now 14.04.