/ 7-21-75 Found 4x6x30 limestone with chisel mark on top
9-5-75 Set large bolt beneath stone and tied out. ① #1

section corner 2-3-10-11 Elmira 10 5-11-
#510205

11-1891 Thos Fraser P462 no 446 & 2. Julius Kemp.
found stone 4x6x30 tested by NW & NE B&T
stumps; proved correct. remarked stone on top.
Meas north - 39.80 3/4 - east 40.03 3/4 to M & L.

4-1892 Thos Fraser. P477 no 456 & 10-11 Yaby & Ferrier
found stone P 462.
1/16 east set stone 4x8x25 glass underneath M & L no mear.
1/16 west set 2 stones 4x4x16 and a wedge shaped stone glass below.
at 19.90 5/8 - see 1/4 3-10.

7-21-75 Found 4x6x30" limestone with chisel mark on top up 12" on N side of old wood fence post in E-W fence

9-5-75 Set large bolt beneath stone and set RR Spikes on N. and E sides.

R.P's Spike and C.S.D. W. side blazed 12" Bur Oak NNE 43.05

Spike and C.S.D. SE side 12" blazed Bur Oak, NE 44.75

Corner 14½' W of 24" Bur Oak tree as corner to fences E-W-N

Section Cor 2-3-10-11 Elmira #510205 #2 (2) 10S--11

8-27-75 (1/16E) Found 4"x8" black mark in clean clay 3½' deep and beneath old road. Also found glass pieces as recorded (removed to office). Set ¾"x20" rod in center of mark and Pepsi bottles along side. Set ¾"x18" rod at surface. Corner is 1'E of fence line N and 2' S of ℄ of road W

Note: Do. Not use

RP CSD S. side pp #2519 NE 41.15'

Note: 9-8-75 Pulled both irons as corner to be set at exact M&L by private survey.

8-27-75 (Center of NW 1/4 Sec 11) Dug in ditch on W side of road and found remaining 15" of 4" x 10" x 24" recorded stone 3' deep and extending down into clay. Set scrap iron around stone. Set 3/4" x 5' rod up to surface. Corner is 20.5' W of ℄ N-S Twp road.
R.P.'s: CSD + Spike W. side 7" blazed Oak SW 38.53'
CSD & Spike E side 20" Walnut NNW 53.52'
Punch hole top W. End Culvert E 6.90'

SECTION 2-3-10-11 ELMIRA 105-11 #510205 (3)

GOV. NOTES - 1853 Wm. A JONES

SET 1/4 post MHL 4000

12" burr oak N47 1/2° E 104 LKS - (68.64)

15" " " N14° W 184 LKS ~~(121.44)~~

15" Red oak S44° W 434 LKS (286.44)

8" W oak S 8° E 403 LKS (265.98)

spring brook 5 LKS WIDE NORTH 250 LKS (165')

"510205" F

9-28-98
mco EA

Sec Cor 2-3-10-11 105-11 Elmira
fd 30" long stone reamy bad dug
out stone and set CIC/p² over
Large bolt set under stone in
(1975) set 30" long stone 1'
North of CIC/p² with post &
sign between

Note: fd 1/16th stones with
Iron between @ 1/16th west
of above Corner in good
Condition