1. 7-2-76 Set 3/4" x 18" shaft #510905 #1

section corner 8 - 9 - 16 - 17 Elmira 10 5 - 11.

5-1875 Hunter P 279 no 276 S 8 J Kuchenbacker.
this corner in dispute. T Desmond and others. 2 blazes ran to
corner - meas from S 1/4 8 indicated it seven east of far blaze.
found 1 standing B tree & 2 likely stumps. Re-set marked
corner by B T S & stumps. 39.75 west to 1/4 cor. undisputed

4-1878 Hunter P 340 no 334 S 9 John Mc Guire
found corner above in place. no meas.

5-22-1900 Robt Fraser P 683 no 607 S 9. Julius Kuckenbacker.
refered to previous surveys no meas - typical Robt Fraser Survey

5-1900 Robt Fraser P 681 no 606. S 8 Salina Kuckenbacher
Corner placed by Hunter gone. or trees mentioned by Hunter.
finally recovered one stump remains and on that and over
of Mrs Kuckenbacher. drove iron bingbolt and took B trees
10" white oak N 47½° E 47 lks. 31.02 Lower foot long.
12" jackoak N 14½° E 27 lks. = 17.82'

6-1902. W Fraser P 40 B. S 17 J Jackson, J Gardner.
found iron stake as corner.
Meas south to temp stake set M & L. 39.82½ = 2628.45

Govt Notes

Set ¼ sec post		40 chs.		
15" white Oak		N 75° E	152 lks	(100.3)
6"	"	N 7° W	19 lks	(12.54)
7"	"	S 13½° W	75 lks	(49.5)
6"	Burr Oak	S 20° E	125 lks	(82.5')

Section Corner 8-9-16-17 Elmira #510905 105-11 #2

6-25-76 Corner comes in old road now cut & washed down to bedrock. Searched for Robert Frazier ringbolt with electronic dip needle. Found nothing. Bearing tree gone.

7-2-76 Set 3/4" x 18" shaft (up 8") in center of old road (now lane) 14.7 N of S lane fence, 10' E of fence line N. and 2' to 3' N of fence E (beginning 100' ± E). Corner set N-S at double W.F. distance from 16-17-20-21 to 1/4 Cor 16-17. Used calculated N-S location of 16-17-20-21 by doubling line from 17-18-19-20 over 1/4 Cor 17-20 and calculated N-S location of 1/4 Cor 16-17 from line of 1/4 Cor 17-18 over 1/16 E. Corner set E-W by prorating R.F. measure from 1/4 Cor 8-17 to

8-9-16-17 against R.F. measure from ¼ Cor 8-9 (found) to ℄ N-S location of 8-9-16-17 as previously determined.

R.P.'s: Spike and CSD N. side 4½" Walnut S77°54'W 39.80

Spike and CSD S. side 5" Walnut N54°55'W 23.50

Spike and CSD N. side of mast N60°40'E 30.97
northerly of twin Jack Oak (blazed 13")

Spike in 24" blazed Oak S23°55'E 89.65
coord.
Bge.