1 9-20-68 set C/M over iron rod. #520406 (1)

¼ corner 4-5 Orion 10 5-12

6-1891 Thos Fraser P452 No 436 & 8 James Campion found stone 4"X6" square on top used in setting S E cor 8 and E ¼ cor 8 on 2 mile measure which overran .8' in 2 miles - did not run line.

8-1968 J Kerr dug twice for corner from center road east over 15 feet, over 2' either side from 7960.45 as record. set ½"x2' rod on section line from NW4 to rod set as SW4 and above chainage.
Rod comes 2 to 3' north fence east and 8 to 10' east of east edge road May dig later with tractor. mej

11.6' to center tele pole LE.
10.4' " " Cor F post ESE.
19.0 " " " " " " NE.

9-20-68 dug again with tractor after running line 2 miles aerial and remeasuring entire line. found rocking but deep sub-soil stones set C/M on line and proportional distances for 2 miles considering orig point records. ~~4~~ 1223 then 3½ - 2640[S] thence 1583.0
actual mens after figuring 3 - 2638.7[S] then 2541.88
- corner lies 19' east of center N-S road
- " on line fence east - 2½' south to fence running west.
- hard nail in corner post east 11.15
- " " " " " " northeast 22.3
- disc in power pole LE 6.4.
Cap in fence post 25' LAW 54.05
- mens actual north to NE cor 5 - 2541.88

1/4 CORNER 4-5 ORION 105-12 #520406 (2)

GOV. NOTES - Oct 6, 1853

South on true line between sections 4+5

Course South

38.53 set gr. section post *

78.53 SEC. CORNER